



Smart HP

PU Exterior Flake Primer 33

SPPUEF-PRIMER33

1L SET (0.8L & 0.2L HARDENER) & 5L SET (4L & 1L HARDENER)



Description

SMART HP PU Exterior Flake Primer 33 is a two component solvent based, flexible polyurethane primer. It is to be used on prepared concrete flooring or steel to provide penetration, wetting and full system flexibility to complement surface and top coat. Product features,

- Excellent wetting of substrate
- Weathering durrability
- Non-yellowing and does not chalk easily
- Good application properties , flow and levelling

Application Area

- Floors (concrete & mosaic tiles)
- Terraces
- Porch
- Toilet

Composition

Pigment	:	Organic and Inorganic Pigment
Binder	:	Polyol & Isocyanate
Volume Solid	:	50%

Properties

Finishing	:	High Sheen
Colour	:	White, Black, Dark Grey & Brown
Density	:	0.98 – 1.10 (Depends on colour)
Pot Life	:	6 – 8 hours
Mixing Ratio	:	4:1 (by volume)
Theoretical Coverage	:	5.31 m2 per litre per coat based on 100 µm dry film thickness (depends on colour) 2.65 m2 per litre per coat based on 200 µm dry film thickness (depends on colour)
Drying Time	:	Touch Dry: About 4 hours (Dependent on temperature and humidity and thickness applied) Hard Dry: About 9 hours (Dependent on temperature and humidity and thickness applied)
Recoating Interval	:	8 hours minimum based on normal condition

Application Method

Brush	:	For normal use thinning is not necessary.
Roller	:	For normal use thinning is not necessary.
Conventional Air Spray	:	Thin with 10 – 20% by volume with PU solvent and adjust to requirement.
Airless Spray	:	Thinning is not usually necessary. Can be thin 5 – 10% volume with PU Solvent to assist application.

Surface Preparation

Remove all loose, defective paint or powdery residues, loose chalk, dust and foreign matter. Repair cracks, uneven surfaces with suitable fillers. Smoothen the putty / filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting. Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH 9.)

Painting Guide

Surface Condition	Sealer (1 coat)	Intermediate coat	Finish (1 - 2 coats)
For Recoat Floor Surface with previous coating cleaned	SMART HP PU Exterior Flake Primer 33	Flakes (optional)	SMART HEAVY DUTY 2K POLYURETHAN EXTERIOR CLEAR 88
New Cement Floor Surface	SMART HP PU Exterior Flake Primer 33	-	Smart HP 2K PU Finish 22

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com



Smart HP PU Exterior Flake Primer 33(Part A)

2 Component Solvent based Polyurethane


0.8 Litres & 4 Litres

Version No. :

Issue Date: 07/06/2024

Safety Data Sheet according to CLASS requirement



SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING		
Product Identifier		
Product Name	Smart HP PU Exterior Flake Primer 33	
Product Code	SPPUEF33-WHITE/BLACK/DARK GREY/BROWN	
Chemical Name	Not Applicable	
Chemical Formula	Not Applicable	
Other means of Identification	2 Component Solvent based Polyurethane	
CAS Number	Not Applicable	
Relevant use of the chemical and restriction		
Relevant identified uses	Use according to manufacturer's directions	
Details of manufacturer / importer		
Registered Company Name	SMART PAINT MANUFACTURING SDN BHD (1031014-A)	
Address	No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.	
Telephone	+607-863 9855	
Fax	+607-861 5055	
Email	info@smart-paints.com	
Web	http://www.smart-paints.com	
Emergency telephone number		
Association / Organisation	Not Applicable	
Emergency telephone number	Not Applicable	
Other emergency telephone number	Not Applicable	
SECTION 2 HAZARDS IDENTIFICATION		
Classification of the substances or mixture		
GHS Classification	Flammable liquids - Category 3 Health Hazard Acute toxicity (Oral) - Category 4 Skin Irritation - Category 2 Aspiration Toxicity - Category 1 Specific Target Organ Toxicity- Single Exposure (Respiratory system) - Category 3 Specific Target Organ Toxicity- Single Exposure (Central nervous system) - Category 3 Environment Hazard Hazardous To The Aquatic Environment – Chronic Hazard - Category 2	
Label elements		
GHS label elements		
Signal word	Warning	
Hazard statement(s)		
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness and dizziness.	
H411	Toxic to aquatic life with long lasting effects.	

Precautionary statement(s)		
	P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P233	Keep container tightly closed.
	P242	Wash thoroughly after handling.
	P243	Take precautionary measures against static discharge.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264	Wash thoroughly after handling.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.

SECTION 2 HAZARDS IDENTIFICATION**Precautionary statement(s) Response**

	P304+P340	IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P302+P352	IF ON SKIN: Wash with plenty of soap and water
	P332+P313	If skin irritation occurs : Get medical advice / attention
	P370+P378	In case of fire: Use dry sand , dry chemical or alcohol-resistant foam to extinguish
	P391	Collect spillage.

Precautionary statement(s) Storage

	P405	Store in locked up.
--	-------------	---------------------

Precautionary statement(s) Disposal

	P501	Dispose of content/ container to appropriate waste site or reclaimer in accordance with local or national regulations.
--	-------------	--

SECTION 3 COMPOSITION / INFORMATION OF INGREDIENTS

CAS number	% [weight]	Name
-	<70	Resin
13463-67-7	<10	Pigment
1330-20-7	<10	Xylene
123-86-4	<8	Butyl Acetate
108-83-8	<2	2,6-dimethylheptan-4-one

SECTION 4 FIRST AID MEASURES**Description of first aid measure**

Eye contact	• Check or and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelid open. Do not use an eye ointment. Seek for medical attention.
Skin contact	• Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an existing dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Get medical attention if redness or irritation occurs.
Inhalation	• High vapour (>1000 ppm) are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anaesthesia. Drowsine unconsciousness and other central nervous system effects. Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth to mouth resuscitation. Administer oxygen if available. Allow the victim to rest in a well ventilated area. Seek medical attention.

SECTION 5 FIREFIGHTING MEASURES**Suitable Fire Extinguishing Media :**

Small fire : Use dry chemical. Foam or CO2.

Large fire : Use water spray. Fog or foam. Water or foam may cause frothing.

Special Protective Actions For Fire Fighters:

Cool container in water spray in order to prevent pressure build-up, auto ignition or explosion. Avoid flushing spilled material into sewers, stream or other bodies of water. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. Respiratory and eye protection are required for fire fighting personnel.

Specific Hazards Arising From The Chemical :

Static discharge, material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapour) and can be dangerous. DO NOT pressurize, cut, Weld braze, solder, drill grind, or expose such containers to heat, flame sparks, static electricity, or other sources of ignition ; they may explode and cause injury or death.

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment And Emergency Procedure****Eye /skin protection :**

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available. Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact. Wear a face shield and chemical resistant clothing such as rubber apron when splashing is likely.

Respiratory Protection :

Use JKKP/NIOSH approved respiratory protection (full face piece recommended) when exposure limits are exceeded.

Ventilation :

Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. If practical, use local mechanical exhaust ventilation at source of air contamination such as open process equipment.

Environment Precaution

Flammable liquid. Ventilate. Eliminate all sources of ignition. Prevent additional discharge of material. For small spills implement cleanup procedure; for large spills implement cleanup procedure and if in public area, keep public away and advise authorities, provide suitable personal protective, dike and contain spill with inert material (sand, earth, etc) and transfer liquid and solid separately to container for recovery or disposal. Report as per regulatory or disposal. Do not use combustible material such as sawdust. Report as per regulatory equipment.

Methods And Materials For Containments And Clean Up

For small liquid spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residue to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose to all salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Remove contaminated soil and dispose of safely.

SECTION 7 HANDLING AND STORAGE**Precautions For Safe Handling**

Avoid smoking and use of open fire. Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial practices.

Condition For Safe Storage ,including Any Incompatibilities

Store in tightly closed original container in well-ventilated area. Avoid exposure to direct sunlight.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control Parameters/ Occupational Limits**

Ingredient/Bahan	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m3	ppm	mg/m3
Acrylic resin	-	-	-	-
Pigment	-	-	-	-
Xylene	100	-	100	435
Butyl Acetate	150	713	150	-
2,6-dimethylheptan-4-one	25	-	25	145

APPROPRIATE ENGINEERING CONTROL MEASURES

If user operations generate dust, fumes, gas, vapours or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emission from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PERSONAL PROTECTION**Respiratory protection**

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Recommended : Full mask with type Cartridge filter.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Recommended : Safety glasses with side-shields.

Skin/ Body Protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Recommended : Wear protective clothing.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance / colour	Liquid/Colour refer catalogue
Odour	Aromatic Hydrocarbon
Solid	59.0 -65.0%
Specific Gravity (@ 25°C)	1.00 -1.05
Viscosity (Ku)	75-80
*Boiling Point	123- 140 oC
*Flash Point	27 – 46 °C
*Melting Point	Not applicable
*Vapour Pressure (@ 20°C)	Not applicable
Vapour Density (101.3 kPa / air=1)	Not applicable
Evaporation Rate (n - Butyl Ether=1)	Not applicable
Lower Flammable Limit LEL / Explosion limit (%)	1.40
Upper Flammable Limit UEL / Explosion limit (%)	7.50
Solubility	Insoluble in water

SECTION 10 STABILITY AND REACTIVITY**REACTIVITY**

No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

Stable under normal temperature conditions and recommended use.

POSSIBILITY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur.

CONDITIONS TO AVOID

Heat, flame , sparks.

Nitric acid, sulfuric acid, strong oxidizing agents.

Electrostatic accumulation hazard? If Yes, use proper grounding procedure.

HAZARDOUS DECOMPOSITION PRODUCTS

Under normal conditions of storage and use, hazardous decompositions products should not be produced.

SECTION 11 TOXICOLOGY INFORMATION

There is no data available on the product itself.

Toxicological information of hazardous ingredients :

Acute toxicity /Ketoksikan Akut**Components/ Komponen:****Butyl Acetate:**

Acute oral toxicity	: LD50 (Rat, male): 12,789 mg/kg
	LD50 (Rat, female): 10,760 mg/kg
Acute inhalation toxicity	: LC50 (Rat, male and female): 0.74 mg/l
Acute dermal toxicity	: LD50 (Rabbit): 14,000 mg/kg

Resin :

Acute oral toxicity	: LD50(rat) : 3.592 mg/kg
Acute inhalation toxicity	: LC50 (rat)/4 Hour : > 6.19 mg/l
Acute dermal toxicity	: LD50(rabbit) : >3.160mg/kg

Skin corrosion/irritation**Components:****Butyl Acetate:**

Species : Rabbit	
Exposure time: 4 hrs	Result : No skin irritation

Serious eye damage/eye irritation**Components :****Butyl Acetate:**

Species : Rabbit	Result : No eye irritation
------------------	----------------------------

Respiratory or skin sensitization**Components:****Butyl Acetate:**

Exposure routes: Inhalation	Remarks: No data available
Exposure routes: Skin contact	Result : Not sensitizing

SECTION 11 TOXICOLOGY INFORMATION**Germ cell mutagenicity****Components:****Butyl Acetate:**

Germ cell mutagenicity

Assessment: Not mutagenic in vivo and in vitro

Carcinogenicity**Components:****Butyl Acetate:**

Carcinogenicity

Assessment : Not classified

Reproductive toxicity**Components:****Butyl Acetate:**

Reproductive toxicity

Assessment : Not classified

STOT - single exposure**Components:****Butyl Acetate:**

Target Organs : Central Nervous System

Assessment : May cause drowsiness or dizziness

Resin :

Target Organs : Central Nervous System

Assessment : May cause drowsiness or dizziness

Target Organs : Respiratory system.

Assessment: May cause respiratory irritation

STOT - repeated exposure**Components:****Butyl Acetate:**

Remarks: Not classified

Aspiration toxicity**Components:****Butyl Acetate:**

Statement on Aspiration Tox. : No data available

SECTION 12 ECOLOGICAL INFORMATION**Ecotoxicity**

No data available.

Persistence And Degradability

No information available.

Bioaccumulative Potential

Has the potential to bioaccumulate.

Mobility In Soil

Floats on water. Adsorbs to soil and has low mobility.

Other Adverse Effects

Do not allow product to reach ground water, water course or sewage system.

Ingredient	Fish 96 hour, LC50 mg/L	Crustacea 48 hour, EC50 mg/L	Algae 72 or 96 hour, ErC50 mg/L
Acrylic resin	92	DNA	DNA
Pigment	DNA	DNA	DNA
Xylene	3.7	DNA	0.799
Butyl Acetate	18	44	397
2,6-dimethylheptan-4-one	30	37.2	DNA

SECTION 13 DISPOSAL INFORMATION**Waste Disposal :**

Recover or recycle if possible. Otherwise dispose in accordance with all applicable with all applicable national environment laws and regulations.

Product Disposal:

This product when dispose of in its unused and uncontaminated state should be treated as a hazardous waste.

Container Disposal :

Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsing as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer. Residue may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Keep container labelled until cleaned and then remove or deface labels.

SECTION 14 TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous Goods (RID) by Rail.

UN Number: 1263

Proper shipping name : Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound.

Class: 3

Packaging Group: III

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG) for the transport of Sea.

UN Number: 1263

Proper shipping name : Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound.

Class : 3

Packaging Group: III

Marine Pollutant: No

SEA (Annex II of MARPOL 73/78 and the IBC Code)/ LAUT (Annex II of MARPOL 73/78 dan the IBC Code) : Not Applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for the transport by Air.

UN Number: 1263

Proper shipping name : Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound.

Class: 3

Packaging Group: III

SECTION 15 REGULATORY INFORMATION

Applicable national regulations :

- a) OSHA 1994 and relevant regulation
- b) Factories and Machinery Act 1967 and relevant regulations
- c) Environment Quality Act 1967 and regulations.
- d) Pesticide Act 1974 and regulations
- e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013
- f) Industry Code Of Practice (On Chemicals Classification And Hazard Communication

SECTION 16 OTHER INFORMATION

Date of preparation: 07-06-2024

Date of revision: -

Version: 01

ABBREVIATION/SINGKATAN

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median Lethal concentration

IACR International Agency for Research in Cancer

CAS Registry Numbers Chemical Abstracts Service Registry Numbers

ICOP Industry Code Of Practice on Chemical Classification and Health approved by Minister under section 37 of the Act

C Ceiling Limit

CEIL Ceiling Limit airborne concentration

STEL Short Term Exposure Limit

DNA Data Not Available

N/R Not Regulated

Disclaimer

All information appearing here in is based on our present state of our knowledge. However the information in this SDS may not be valid for such material used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or completeness. We do not accept liability for any loss or damage that may occur from the use of this information.



Smart HP 2K PU Exterior Flake Primer 33 (Hardner-Part B)

Hardener for 2 Component Solvent based Polyurethane


0.2L & 1L

Version No. : 2.1.24

Issue Date: 05/06/2024

Safety Data Sheet according to CLASS requirement



SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING		
Product Identifier		
Product Name	Smart HP 2K PU Exterior Flake Primer 33 - Hardener (Part B)	
Product Code	SPPUEF33-HD	
Chemical Name	Not Applicable	
Chemical Formula	Not Applicable	
Other means of Identification	Hardener for 2 Component Solvent based Polyurethane	
CAS Number	Not Applicable	
Relevant use of the chemical and restriction		
Relevant identified uses	Use according to manufacturer's directions	
Details of manufacturer / importer		
Registered Company Name	SMART PAINT MANUFACTURING SDN BHD (1031014-A)	
Address	No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.	
Telephone	+607-863 9855	
Fax	+607-861 5055	
Email	info@smart-paints.com	
Web	http://www.smart-paints.com	
Emergency telephone number		
Association / Organisation	Not Applicable	
Emergency telephone number	Not Applicable	
Other emergency telephone number	Not Applicable	
SECTION 2 HAZARDS IDENTIFICATION		
Classification of the substances or mixture		
GHS Classification	<p>Physical Hazard Flammable liquids - Category 3</p> <p>Health Hazard Acute toxicity (Oral) - Category 4 Skin Sensitization - Category 1 Specific target organ toxicity -Single exposure (irritating to respiratory system) - Category 3 Respiratory sensitization - Category 1</p> <p>Environment Hazard Hazardous to the aquatic environment -acute - Category 3 Hazardous to the aquatic environment -chronic - Category 3</p>	
Label elements		
GHS label elements		
Signal word	Warning	
Hazard statement(s)		
H226	Flammable liquid and vapour.	
H332	Harmful if swallowed.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H317	May cause an allergic skin reaction.	
H335	May cause respiratory irritation.	
H402	Harmful to aquatic life.	
H412	Harmful to aquatic life with long lasting effects.	

Precautionary statement(s)		
	P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	P233	Wear protective gloves/protective clothing/eye protection/face protection.
	P241	Use explosion-proof electrical/ ventilating/lighting equipment.
	P242	Obtain special instructions before use.
	P243	Do not handle until all safety precautionary have been read and understood.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P280	Use personal protective equipment as required.
	P271	Use only outdoors or in a well-ventilated area.
	P272	Contaminated work clothing shall not be allowed out of the workplace.

SECTION 2 HAZARDS IDENTIFICATION**Precautionary statement(s) Response**

	P302+P352	IF ON SKIN : Wash with plenty of water and soap.
	P332+P313	If skin irritation occurs : Get medical advice / attention
	P303+P361+P353	IF ON SKIN (or hair) : Remove /take off immediately all contaminated clothing. Rinse skin with water/ shower.
	P370+P378	Take off contaminated clothing and was before reuse.
	P391	Collect spillage.

Precautionary statement(s) Storage

	P405	Store in locked up.
--	-------------	---------------------

Precautionary statement(s) Disposal

	P501	Dispose of content/ container to appropriate waste site or reclaimer in accordance with local or national regulations.
--	-------------	--

SECTION 3 COMPOSITION / INFORMATION OF INGREDIENTS

CAS number	% [weight]	Name
28182-81-2	>=50.0 - <=100.0	Hexamethylene diisocyanate isocyanurate-type oligomers
1330-20-7	>=7.0 - < 15.0	Xylene
100-41-4	>=0.0 < 3.0	Ethylbenzene
822-06-0	0 - 0.3	1,6-hexamethylene diisocyanate

SECTION 4 FIRST AID MEASURES**Description of first aid measure**

Eye contact	• Check or and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelid open. Do not use an eye ointment. Seek for medical attention.
Skin contact	• Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an exiting dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Get medical attention if redness or irritation occurs.
Inhalation	• High vapour (>1000 ppm) are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anaesthesia. Drowsine unconsciousness and other central nervous system effects. Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth to mouth resuscitation. Administer oxygen if available. Allow the victim to rest in a well ventilated area. Seek medical attention.

SECTION 5 FIREFIGHTING MEASURES**Suitable Fire Extinguishing Media :**

Small fire : Use dry powder, Foam.
Large fire : Use water spray. Fog or foam. Water or foam may cause frothing.

Special Protective Actions For Fire Fighters:

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Specific Hazards Arising From The Chemical :

Hazards during fire-fighting: harmful vapours
Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment And Emergency Procedure**

Use personal protective clothing. Breathing protection required.
Can release flammable vapours. Wind direction should be noted.
Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environment Precaution

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods And Materials For Containments And Clean Up

For large amounts: Pump off product.
For residues: Pick up with suitable absorbent material.
Dispose of absorbed material in accordance with regulations

SECTION 7 HANDLING AND STORAGE**Precautions For Safe Handling**

Avoid smoking and use of open fire. Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial practices.

Condition For Safe Storage ,including Any Incompatibilities

Store in tightly closed original container in well-ventilated area. Avoid expose to direct sunlight.

Storage stability:

If moisture enters isocyanate containers, CO2 forms and pressure builds up.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**Control Parameters/ Occupational Limits**

Ingredient/Bahan	ACGIH TLV-TWA		OSHA PEL-TWA	
	ppm	mg/m3	ppm	mg/m3
Ethylbenzene	20			
1,6-hexamethylene	0.005	-	-	-
Xylene	100		150	

APPROPRIATE ENGINEERING CONTROL MEASURES

If user operations generate dust, fumes, gas, vapours or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Emission from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PERSONAL PROTECTION**Respiratory protection**

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Recommended : Full mask with type Cartridge filter.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Recommended : Safety glasses with side-shields.

Skin/ Body Protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Recommended : Wear protective clothing.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance / colour	Liquid/Colourless
Odour	Faint odour
Solid	Not applicable
Specific Gravity (@ 25°C)	1.06
Viscosity (Ku)	Not applicable
*Boiling Point	120 °C
*Flash Point	39.5 °C
*Melting Point	-25 °C
*Vapour Pressure (@ 20°C)	< 10 mbar
Vapour Density (101.3 kPa / air=1)	Not determined
Evaporation Rate (n - Butyl Ether=1)	Not determined
Lower Flammable Limit LEL / Explosion limit (%)	1.0% (V)
Upper Flammable Limit UEL / Explosion limit (%)	10.8% (V)
Solubility	React with water

SECTION 10 STABILITY AND REACTIVITY**REACTIVITY**

No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

Stable under normal temperature conditions and recommended use.

POSSIBILITY OF HAZARDOUS REACTION

Reacts with alcohols. Reacts with amines. Reacts with substances which contain active hydrogen. Reacts with water, with formation of carbon dioxide. The formation of gaseous decomposition products builds up pressure in tightly closed containers. Vapours may form ignitable mixture with air.

CONDITIONS TO AVOID

Avoid moisture. See SDS section 7 - Handling and storage.

HAZARDOUS DECOMPOSITION PRODUCTS

Decomposition products:

No applicable information available.

Thermal decomposition:

No decomposition if used correctly

SECTION 11 TOXICOLOGY INFORMATION**Primary routes of exposure**

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects**Oral**

Type of value: LD50

Species: rat

Value: > 5,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

Type of value: ATE

Species: rat

Value: > 1 - 5 mg/l

Exposure time: 4 h

The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal

Type of value: ATE

Species: rat

Value: not determined

Skin

Species: rabbit

Result: non-irritant

Method: OECD Guideline 404

The product has not been tested. The statement has been derived from the properties of the individual components.

Eye

Species: rabbit

Result: non-irritant

Method: OECD Guideline 405

The product has not been tested. The statement has been derived from the properties of the individual components.

Sensitization**Aspiration Hazard**

No aspiration hazard expected.

Chronic Toxicity/Effects**Repeated dose toxicity**

Information on: 1-methoxy-2-propylacetate

Assessment of repeated dose toxicity: Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The substance may cause damage to the olfactory epithelium after repeated inhalation. Repeated oral uptake of the substance did not cause substance-related effects.

Information on: xylene

Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity.

Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney

Genetic toxicity

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: No data available concerning carcinogenic effects.

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Teratogenicity

Assessment of teratogenicity: Based on the ingredients, there is no suspicion of a teratogenic effect

SECTION 11 TOXICOLOGY INFORMATION**Genetic toxicity**

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: No data available concerning carcinogenic effects.

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Teratogenicity

Assessment of teratogenicity: Based on the ingredients, there is no suspicion of a teratogenic effect

SECTION 12 ECOLOGICAL INFORMATION**Toxicity****Aquatic toxicity**

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

The product has not been tested. The statement has been derived from the properties of the individual components.

Toxicity to fish

LC50 (96 h) 10 - 100 mg/l, Brachydanio rerio

The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates

EC50 10 - 100 mg/l, Daphnia magna

The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic plants

EC50 (72 h) 10 - 100 mg/l, algae

The product has not been tested. The statement has been derived from the properties of the individual components.

Chronic toxicity to fish

No data available.

Chronic toxicity to aquatic invertebrates

No data available

Microorganisms/Effect on activated sludge**Toxicity to microorganisms**

bacteria/EC50 (3 h): > 1,000 mg/l

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. The product has not been tested. The statement has been derived from the properties of the individual components.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

The substance can be virtually eliminated from water in suitable effluent treatment plants by biodegradation, stripping and mechanical separation.

Elimination information

Not readily biodegradable (by OECD criteria).

Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters. The local regulations on waste-water treatment must be followed.

SECTION 13 DISPOSAL INFORMATION**Waste Disposal :**

Recover or recycle if possible. Otherwise dispose in accordance with all applicable with all applicable national environment laws and regulations.

Product Disposal:

This product when dispose of in its unused and uncontaminated state should be treated as a hazardous waste.

Container Disposal :

Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsing as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer. Residue may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Keep container labelled until cleaned and then remove or deface labels.

SECTION 14 TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous Goods (RID) by Rail.

UN Number: 1263

Proper shipping name : Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound).

Class: 3

Packaging Group: III

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG) for the transport of Sea.

UN Number: 1263

Proper shipping name : Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound).

Class : 3

Packaging Group: III

Marine Pollutant: No

SEA (Annex II of MARPOL 73/78 and the IBC Code)/ LAUT (Annex II of MARPOL 73/78 dan the IBC Code) : Not Applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for the transport by Air.

UN Number: 1263

Proper shipping name : Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound).

Class: 3

Packaging Group: III

SECTION 15 REGULATORY INFORMATION

Applicable national regulations :

- a) OSHA 1994 and relevant regulation
- b) Factories and Machinery Act 1967 and relevant regulations
- c) Environment Quality Act 1967 and regulations.
- d) Pesticide Act 1974 and regulations
- e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013
- f) Industry Code Of Practice (On Chemicals Classification And Hazard Communication

SECTION 16 OTHER INFORMATION

Date of preparation: 05-06-2024

Date of revision: -

Version: 01

ABBREVIATION/SINGKATAN

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value

TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median Lethal concentration

IACR International Agency for Research in Cancer

CAS Registry Numbers Chemical Abstracts Service Registry Numbers

ICOP Industry Code Of Practice on Chemical Classification and Health approved by Minister under section 37 of the Act

C Ceiling Limit

CEIL Ceiling Limit airborne concentration

STEL Short Term Exposure Limit

DNA Data Not Available

N/R Not Regulated

Disclaimer

All information appearing here in is based on our present state of our knowledge. However the information in this SDS may not be valid for such material used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or completeness. We do not accept liability for any loss or damage that may occur from the use of this information.