



Smart Epoxy Tile Flake Epoxy Tile Flake 1Kg

Version No. : **4.1.19** Issue Date: **14.11.2022**

Safety Data Sheet according to CLASS requirement



ECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING				
Product Identifier				
Product Name	Smart Epoxy Tile Flake			
Product Code	SPETF			
Chemical Name	Not Applicable			
Chemical Formula	Not Applicable			
Other means of Identification	Flakes			
CAS Number	Not Applicable			
Relevant use of the chemical and restriction				
Relevant identified uses	Use according to manufacturer's directions			
Details of manufacturer / importer Registered Company Name	s of manufacturer / importer Registered Company Name SMART PAINT MANUFACTURING SDN BHD (1031014-A)			
Address	No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.			
Telephone	+607-863 9855			
Fax	+607-861 5055			
Email	info@smart-paints.com			
Web	http://www.smart-paints.com			
Emergency telephone number				
Association / Organisation	Not Applicable			
Emergency telephone number	Not Applicable			
Other emergency telephone number	Not Applicable			

SECTION 2 HAZARDS IDENTIFICATION					
Classification of the substances or mixture					
Health Hazard					
Eyes Iritation	Cause Eye Iritation (Itching or redness) upon direct contact				
Skin	Mild Irrittation (Itching/ redness)				
Ingestion	Symptom Include gastro intestinal tract upset and diarrhea				
Inhalation	Cause Respiratory tract irritation (Coughing, wheezing, shortness of breath)				
Environment Hazard Hazardous To The Aquatic Environment - Not Available					
Precautionary statement(s)					
Keep container tightly closed					
Wear protective gloves/protective clothing/eye protection/face protection.					
Obtain special instructions before use.					
Do not handle until all safety precautionary have been read and understood.					
Use personal protective equipment as required.					
Wash thoroughly after handling.					
	Eyes Iritation Skin Ingestion Inhalation Environment Hazard Hazardous To The Aqu Keep container tightly cl Wear protective gloves/I Obtain special instructio Do not handle until all sa Use personal protective				

SECTION 2 HAZARDS IDENTIFICATION				
Precautionary statement(s) Response				
P308+P313	IF exposed or concerned : Get medical advice / attention.			
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest.			
P342+P311	If experiencing respiratory symptoms : CALL a POISON CENTER or doctor / physician .			
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.			
P363	Wash contaminated clothing before reuse.			
Precautionary statement(s) Storage				
P403+P235	Store in a well - ventilated place. Keep cool.			
P405	5 Store in locked up.			
recautionary statement(s) Disposal				
P501	Dispose of content/ container to appropriate waste site or reclaimer in accordance with local or national regulations.			

SECTION 3 COMPOSITION / INFORMATION OF INGREDIENTS

SECTION 4 FIRST AID MEASURES	
Description of first aid measure	
Eye contact	Check or and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelid open. Do not use an eye ointment. Seek for medical attention.
Skin contact	Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an exiting dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abbrasive soap. Get medical attention if redness or irritation occurs.
Inhalation	High vapour (>1000 ppm) are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anaesthesia. Drowsine unconsciousness and other central nervous system effects. Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth to mouth resuscitation. Administer oxygen if available. Allow the victim to rest in a well ventilated area. Seek medical attention.

SECTION 5 FIREFIGHTING MEASURES

Suitable Fire Extinguishing Media:

Small fire : Use dry chemical. Foam or CO2.

Large fire : Use water spray. Fog or foam. Water or foam may cause frothing.

Special Protective Actions For Fire Fighters:

Cool container in water spray in order to prevent pressure build-up, auto ignition or explosion. Avoid flushing spilled material into sewers, stream or other bodies of water. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. Respiratory and eye protection are required for fire fighting personnel.

Specific Hazards Arising From The Chemical:

Static discharge, material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapour) and can be dangerous. DO NOT pressurize, cut. Weld braze, solder, drill grind, or expose such containers to heat, flame sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment And Emergency Procedure

Eye /skin protection :

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available. Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact. Wear a face shield and chemical resistant clothing such as rubber apron when splashing is likely.

Respiratory Protection:

Use JKKP/NIOSH approved respiratory protection (full face piece recommended) when exposure limits are exceeded.

Ventilation :

Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. If practical, use local mechanical exhause ventilation at source of air contamination such as open process equipment.

Environment Precaution

Flammable liquid. Ventilate. Eliminate all sources of ignition. Prevent additional discharge of material. For small spills implement cleanup procedure; for large spills implement cleanup procedure and if in public area, keep public away and advice authorities, provide suitable personal protective, dike and contain spill with inert material (sand, earth, etc) and transfer liquid and solid separately to container for recovery or disposal. Report as per regulatory or disposal. Do not use combustible material such as sawdust. Report as per regulatory equipment.

Methods And Materials For Containments And Clean Up

For small liquid spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residue to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose to all salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Remove contaminated soil and dispose of safely.

Smart Epoxy Tile Flake Issue Date: 14.11.2022

Version 4.1.19

SECTION 7 HANDLING AND STORAGE

Precautions For Safe Handling

Avoid smoking and use of open ire. Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial practices.

Condition For Safe Storage ,including Any Incompatibilities

Store in tightly closed original container in well-ventilated area. Avoid expose to direct sunlight.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters/ Occupational Limits

	ACGIH TLV-TWA	OSHA PEL-TWA	
Ingredient/Bahan	ppm mg/m3	ppm mg/m3	

APPROPRIATE ENGINEERING CONTROL MEASURES

If user operations generate dust, fumes, gas, vapours or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emission from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PERSONAL PROTECTION

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: Full mask with type Cartridge filter.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products I a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations.

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Recommended : Safety glasses with side-shields.

Skin/ Body Protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Recommended : Wear protective clothing

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES		
Appearance	Flake or Powder in different colour	
Odour	Odorless	
Specific Gravity @ 25°c	0.4-0.8 g/cm ³	
Solubility	Insoluble in water	
Boiling Point	Not Applicable	
рН	6.8-7.5	

SECTION 10 STABILITY AND REACTIVITY

REACTIVITY

No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

Stable under normal temperature conditions and recommended use.

POSSIBILTY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur.

CONDITIONS TO AVOID

Heat, flame, sparks.

Nitric acid, sulfuric acid, strong oxidizing agents.

Electrostatic accumulation hazard? If Yes, use proper grounding procedure.

HAZARDOUS DECOMPOSITION PRODUCTS

Under normal conditions of storage and use, hazardous decompositions products should not be produced.

Smart Epoxy Tile Flake Issue Date: 14.11.2022

Version 4.1.19

Chronic Toxicity

SECTION 11 TOXICOLOGY INFORMATION

Acute Toxicity Not Applicable

Target Organs Respiratory System, Eyes

Not Applicable

Tetratogenicity Not Applicable Embryortoxicity Not Applicable Genotoxicity Not Applicable Reproductive Toxicity Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence And Degradability

No information available

Bioaccumulative Potential

Has the potential to bioaccumulate.

Mobility In Soil

Floats on water. Adsorbs to soil and has low mobility.

Other Adverse Effects

Do not allow product to reach ground water, water course or sewage system.

SECTION 13 DISPOSAL INFORMATION

Waste Disposal :

Recover or recycle if possible. Otherwise dispose in accordance with all applicable with all applicable national environment laws and regulations.

Product Disposal:

This product when dispose of in its unused and uncontaminated state should be treated as a hazardous waste.

Container Disposal:

Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsing as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer. Residue may cause an explosion hazard. Do not pincture, cut or weld uncleaned drums. Keep container labelled until cleaned and then remove or deface labels.

SECTION 14 TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for air.

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous Goods (RID) by Rail.

UN Number: 1263

Proper shipping name: Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound. Class: 3

Packaging Group: III

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG) for the transport of Sea.

Proper shipping name: Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound.

Class : 3

Packaging Group: III Marine Pollutant: No

SEA (Annex II of MARPOL 73/78 and the IBC Code) / LAUT (Annex II of MARPOL 73/78 dan the IBC Code) : Not Applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for the transport by Air.

Proper shipping name: Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound

Class: 3 Packaging Group: III Smart Epoxy Tile Flake Issue Date: 14.11.2022

Version 4.1.19

SECTION 15 REGULATORY INFORMATION

Applicable national regulations :

- a) OHSA 1994 and relevant regulation
- b) Factories and Machinery Act 1967 and relevant regulations
- c) Environment Quality Act 1967 and regulations.
- d) Pesticide Act 1974 and regulations
- e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013
- f) Industry Code Of Practice (On Chemicals Classification And Hazard Communication

SECTION 16 OTHER INFORMATION

Date of preparation: 14-11-2022

Date of revision: -Version: 01

ABBREVIATION/SINGKATAN

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration PEL Permissible Exposure Limit

LD50 Lethal Dose

Median Lethal concentration

IACR International Agency for Research in Cancer

CAS Registry Numbers Chemical Abstracts Service Registry Numbers
ICOP Industry Code Of Practice on Chemical Classification and Health approved by Minister under section 37 of the Act

Ceiling Limit

Ceiling Limit airborne concentration CEIL

STEL Short Term Exposure Limit

DNA Data Not Available N/R Not Regulated

All information appearing here in is based on our present state of our knowledge. However the information in this SDS may not be valid for such material used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or completeness. We do not accept liability for any loss or damage that may occur from the use of this information.