



Smart Epoxy Tile Primer (100% solid, Solvent Free) Epoxy Tile Primer Solvent Free

0.74KG (Part A)

Version No. : **3.2.16**Issue Date: **10.11.2022**

Safety Data Sheet according to CLASS requirement



SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING Product Identifier				
Product Code	SPETP-Primer			
Chemical Name	Not Applicable			
Chemical Formula	Not Applicable			
Other means of Identification	Epoxy Tile Primer Solvent Free			
CAS Number	Not Applicable			
Relevant use of the chemical and restriction				
Relevant identified uses	Use according to manufacturer's directions			
Details of manufacturer / importer				
Registered Company Name				
Address	No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang, 81800 Ulu Tiram, Johor, Malaysia.			
Telephone	+607-863 9855			
Fax	+607-861 5055			
Email	info@smart-paints.com			
Web	http://www.smart-paints.com			
Emergency telephone number				
Association / Organisation	Not Applicable			
Association / Organisation Emergency telephone number	Not Applicable Not Applicable			

SECTION 2 HAZARDS IDENTIFICATION				
Classification of the substances or mixture				
GHS Classification	Health Hazard Skin Corrosion/ irritation - Category 3 Serious Eye Damage/ Eye Irritation - Category 2B Skin Sensitizer - Category 1 Environment Hazard Hazardous To The Aquatic Environment - Chronic Hazard - Category 3			
Label elements				
GHS label elements	<u>(!</u>)			
Signal word	Warning			
Hazard statement(s)				
H316	May cause mild skin irritating			
H317	May cause allergic skin reaction.			
H320	May cause eye irritating.			

Precautionary statement(s)		
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P332 + 337+ 350+ 313	If skin/eyes irritation occurs, wash with plenty of soap and water and get medical advice/ attention.	
P202	Do not handle until all safety precautionary have been read and understood.	
P281	Use personal protective equipment as required.	
P264	Wash thoroughly after handling.	
P285	In case of inadequate ventilation wear respiratory protection.	
P264	Wash thoroughly after handling.	

Contaminated work clothing shall not be allowed out of the workplace.

Avoid release to the environment.

P272

P273

SECTION 2 HAZARDS IDENTIFICATION Precautionary statement(s) Response				
P301+P310 P331				
P308+P313				
P304+P341				
P342+P311	If experiencing respiratory symptoms: CALL a POISON CENTER or doctor / physician. IF ON SKIN: Wash with plenty of water and soap. Specific treatment (see information on this label).			
P302+P352				
P321				
P332+P313	If skin irritation occurs: Get medical advice / attention Take off contaminated clothing and was before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.			
P362				
P304+P340				
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.			
P333+P313	If skin irritation or rash occurs: Get medical advice / attention.			
P363	Wash contaminated clothing before reuse.			
Precautionary statement(s) Storage				
P403+P235 P405 P403+P233	Store in a well - ventilated place. Keep cool. Store in locked up. Store in a well - ventilated place. Keep container tightly closed.			
Precautionary statement(s) Disposal				
P501	Dispose of content/ container to appropriate waste site or reclaimer in accordance with local or national regulations.			

CAS number	% [weight]		Name	
-	< 13%	Diluent		
-	< 80%	Resin		
-	< 0.1%	Additive		

SECTION 4 FIRST AID MEASURES				
Description of first aid measure				
Eye contact	Check or and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelid open. Do not use an eye ointment. Seek for medical attention.			
Skin contact	Frequent or prolonged contact may irritate and cause dermatitis. Skin contact may aggravate an exiting dermatitis condition. Remove contaminated clothing – launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abbrasive soap. Get medical attention if redness or irritation occurs.			

Issue Date: **10.11.2022**

Version 3.2.16

SECTION 5 FIREFIGHTING MEASURES

Suitable Fire Extinguishing Media:

Small fire : Use dry chemical. Foam or CO2.

: Use water spray. Fog or foam. Water or foam may cause frothing. Large fire

Special Protective Actions For Fire Fighters:

Cool container in water spray in order to prevent pressure build-up, auto ignition or explosion. Avoid flushing spilled material into sewers, stream or other bodies of water. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. Respiratory and eye protection are required for fire fighting personnel.

Specific Hazards Arising From The Chemical:

Static discharge, material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapour) and can be dangerous. DO NOT pressurize, cut. Weld braze, solder, drill grind, or expose such containers to heat, flame sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment And Emergency Procedure

Eye /skin protection:

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment immediately available. Wear appropriate protective clothing and chemical resistant gloves to prevent skin contact. Wear a face shield and chemical resistant clothing such as rubber apron when splashing is likely. Respiratory Protection:

Use JKKP/NIOSH approved respiratory protection (full face piece recommended) when exposure limits are exceeded.

Ventilation :

Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. If practical, use local mechanical exhause ventilation at source of air contamination such as open process equipment.

Environment Precaution

Flammable liquid. Ventilate. Eliminate all sources of ignition. Prevent additional discharge of material. For small spills implement cleanup procedure; for large spills implement cleanup procedure and if in public area, keep public away and advice authorities, provide suitable personal protective, dike and contain spill with inert material (sand, earth, etc) and transfer liquid and solid separately to container for recovery or disposal. Report as per regulatory or disposal. Do not use combustible material such as sawdust. Report as per regulatory equipment.

Methods And Materials For Containments And Clean Up

For small liquid spills (<1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residue to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose to all salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Remove contaminated soil and dispose of safely.

SECTION 7 HANDLING AND STORAGE

Precautions For Safe Handling

Avoid smoking and use of open ire. Avoid inhalation of vapours and contact with skin and eyes. Observe good industrial practices

Condition For Safe Storage ,including Any Incompatibilities

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Store in tightly closed original container in well-ventilated area. Avoid expose to direct sunlight.

Control Parameters/ Occupational Limits ACGIH TLV-TWA **OSHA PEL-TWA** Ingredient/Bahan ppm mg/m3 ppm mg/m3

APPROPRIATE ENGINEERING CONTROL MEASURES

If user operations generate dust, fumes, gas, vapours or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emission from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PERSONAL PROTECTION

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: Full mask with type Cartridge filter.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products I a risk assessment indicates this is necessary. After contamination with product change the gloves immediately and dispose of them according to relevant national and local regulations

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Recommended: Safety glasses with side-shields.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Recommended: Wear protective clothing

Issue Date: 10.11.2022

Issue Date: 10.11.2022

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES Appearance / colour Liquid / White **Pigment** < 9% 100.0% Solid Specific Gravity (@ 25°C) 1.19 Viscosity (Ku) Not applicable *Boiling Point Not applicable *Melting Point Not applicable *Vapour Pressure (@ 20°C) Not applicable Not applicable Vapour Density (101.3 kPA / air=1) Evaporation Rate (n - Butyl Ether=1) Not applicable Insoluble in water

SECTION 10 STABILITY AND REACTIVITY

No dangerous reaction known under condition of normal use.

CHEMICAL STABILITY

Stable under normal temperature conditions and recommended use.

POSSIBILTY OF HAZARDOUS REACTION

Under normal conditions of storage and use, hazardous reaction will not occur.

Odour

CONDITIONS TO AVOID

Heat, flame, sparks.

Nitric acid, sulfuric acid, strong oxidizing agents.

Electrostatic accumulation hazard? If Yes, use proper grounding procedure.

HAZARDOUS DECOMPOSITION PRODUCTS

When expose to high temperature, may produce hazardous decomposition products such as Carbon monoxide ,carbon dioxide, smoke and oxides of nitrogen

SECTION 11 TOXICOLOGY INFORMATION

There is no data available on the product itself.

Toxicological information of hazardous ingredients :

: Not Classified Acute toxicity Skin corrosion/ irritation : Drv skin Serious eye /damage irritation Not Classified Respiratory sensitization May lead to dermatitis Germ cell mutagenicity Not classified : Not Classified Carcinogenicity Reproductive toxicity : No data available Specific target organ toxicity (single exposure) No data available Specific target organ toxicity (repeated exposure): Not classified Aspiration hazard No data available Symptoms/injuries after inhalation : No data available

No data available Symptoms/injuries after skin contact Symptoms/injuries after eye contact : Not Classified Symptoms/injuries after eye ingestion Not Classified Chronic symptoms : Not Classified

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity

No data available.

Persistence And Degradability

No information available.

Bioaccumulative Potential

Has the potential to bioaccumulate.

Mobility In Soil

Floats on water. Adsorbs to soil and has low mobility.

Other Adverse Effects

Do not allow product to reach ground water, water course or sewage system.

Version 3.2.16

SECTION 13 DISPOSAL INFORMATION

Waste Disposal:

Recover or recycle if possible. Otherwise dispose in accordance with all applicable with all applicable national environment laws and regulations.

Product Disposal:

This product when dispose of in its unused and uncontaminated state should be treated as a hazardous waste.

Container Disposal:

Drain container thoroughly. Rinse three times with suitable solvent. Treat rinsing as for product disposal. After draining, vent in a safe place away from sparks and fire. Send drum recoverer or metal reclaimer. Residue may cause an explosion hazard. Do not pincture, cut or weld uncleaned drums. Keep container labelled until cleaned and then remove or deface labels.

SECTION 14 TRANSPORT INFORMATION

Transport to be in accordance with ADR/RID for road/rail, IMDG for sea and IATA for air.

LAND TRANSPORT

Classified as Dangerous Goods by the criteria of the European Agreement concerning the international carriage of Dangerous Goods (ADR) by Road & Regulations concerning the international carriage of Dangerous Goods (RID) by Rail.

UN Number: 1263

Proper shipping name : Paint (including paint, lacquer,enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound.

Class: 3

Packaging Group: III

SEA TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG) for the transport of Sea.

Proper shipping name : Paint (including paint, lacquer,enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound.

Class : 3

Packaging Group: III

Marine Pollutant: No

SEA (Annex II of MARPOL 73/78 and the IBC Code)/ LAUT (Annex II of MARPOL 73/78 dan the IBC Code) : Not Applicable

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for the transport by Air.

UN Number: 1263

Proper shipping name: Paint (including paint, lacquer, enamel, stain, shellac, varnish, liquid filler and liquid lacquer base) or paint related material (including paint thinning or reducing compound.

Class: 3

Packaging Group: III

SECTION 15 REGULATORY INFORMATION

Applicable national regulations

- a) OHSA 1994 and relevant regulation
- b) Factories and Machinery Act 1967 and relevant regulations
- c) Environment Quality Act 1967 and regulations.
- d) Pesticide Act 1974 and regulations
- e) Occupational Safety and Health (Classification, Labelling And Safety Data Sheet of Hazardous Chemicals) Reg 2013
- f) Industry Code Of Practice (On Chemicals Classification And Hazard Communication

SECTION 16 OTHER INFORMATION

Date of preparation: 10-11-2022

Date of revision: -Version: 01

ABBREVIATION/SINGKATAN

ACGIH American Conference of Governmental Industrial Hygienists

TLV Threshold limit value TWA Time-Weighted Average

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

LD50 Lethal Dose

LC50 Median Lethal concentration

IACR International Agency for Research in Cancer

Chemical Abstracts Service Registry Numbers CAS Registry Numbers

Industry Code Of Practice on Chemical Classification and Health approved by Minister under section 37 of the Act ICOP

Ceiling Limit

CEIL Ceiling Limit airborne concentration STEL Short Term Exposure Limit

DNA Data Not Available N/R Not Regulated

All information appearing here in is based on our present state of our knowledge. However the information in this SDS may not be valid for such material used in combination with any other materials or in any process. No representation, warranty or guarantee is made as to its accuracy, reliability or completeness. We do not accept liability for any loss or damage that may occur from the use of this information.

Issue Date: 10.11.2022