

# **Smart Penetrating Primer**

SPP

1, 5 & 18 Litre

# Description

**Penetrating Primer** is specially formulated using modified acrylic emulsion. It is specially designed to apply on skim coated wall and plaster ceiling which is powdery in nature to enhance the inter-coat bonding for top finishing coat.

## Main Features

Good for chalky and powdery surface.

# Usage

Exterior wall, interior wall and ceiling.

## Composition

Appearance/ Colour : Small amount of organic blue tinter

Polymer : Modified Acrylic Emulsion

Volume Solid : -

Diluent : Water

## **Properties**

Finishing : Clear Light Blue Colour : Light Blue Theoritical Coverage : 9 -11 m2/L Drying Time (at 25°C) : 15 Minutes Recoat : 1 hours Curing Time (at 25°C) : 24 hours

## **Application Method**

- 1. Fix the water leakage before apply this product to substrate
- 2. Scrap away loose paint film (if have)
- 3. Patching cracking area (if have)
- 4. Apply 1-2 coats of Smart Penetrating Primer (recoat 1 hour)
- 5. Let it dry for 1 hour.
- 6. After dry 24 hours, can continue to apply Smart Green Sealer 850/ Smart Eco Sealer and desired top coat finish.



#### Surface Preparation

Remove all loose, defective paint or powdery residues, loose chalk, dust and foreign matter. Repair cracks, uneven surfaces with suitable fillers. Smoothen the putty / filler areas with sand paper. Surfaces to be painted must be cleaned thoroughly and dry, it must be free from dirt, grease and other foreign matters. Allow all surfaces to dry completely prior to painting.

Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 16% measured by protimeter and alkalinity of the walls to be below pH9.) Spot prime with Penetrating Primer.

#### **Storage Condition**

Store in unopened and undamaged packaging in dry condition. Protect from direct sunlight.

#### Shelf life

12 months when unopened in original packaging and stored in a dry cool place.

#### Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.

No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,

81800 Ulu Tiram, Johor, Malaysia

Telephone No. : +607-863 9855 (Hunting Line) Fax No.: +607-861 5055

Email : info@smart-paints.com