



Smart Vinyl Glo Extra Clean

SPVGEC/ SPTBVGEC

1 Litre, 5 Litres & 15 Litres



Description

Smart Vinyl Glo Extra Clean is a low VOC acrylic based paint which is specially formulated to provide a healthy living environment for the family. This anti-bacterial paint provides protection from bacteria which promotes better hygiene and health. It is an ideal paint for use in homes, schools and food preparation areas. Smart Vinyl Glo Extra Clean protects the environment from any types of bacteria such as E-Coli and Staphylococcus Aureus (Tested by SGS Testing). It provides a mid-sheen wall finish that is able to enhance the indoor surface with luxurious feel while protecting the wall at the same time.

Usage

For decoration and protective of wall, ceiling, plaster, brickworks, cement board for a Luxury Decorative Mid Sheen Finish. Easily maintained by cleaning with a damp cloth.

Composition

Pigment	:	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	:	Acrylic based emulsion.
Volume Solid	:	White 38% (Nominal), other colours will vary.
Diluent	:	Water

Properties

Finishing	:	Mid Sheen Luxury Finish.
Colour	:	A wide range of colours. Please refer Smart Vinyl Glo Colour Card.
Theoretical Coverage	:	10 – 12 m ² /Litre
Drying Time	:	Touch dry – 30 to 60 minutes. *Dependent on temperature and humidity.
Recoating Interval	:	1 to 2 hours.

Application Method

Brush	:	For normal use thinning is not necessary.
Roller	:	For normal use thinning is not usually necessary. Can be thin 5 -10% by volume with water to assist application.
Conventional Air Spray	:	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	:	Thinning is not necessary. Can be thin 5 - 10% by volume with water to assist application.

Surface Preparation

- Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and wax. (To have a better finish, rub down surface using suitable abrasive and dust off.)
- If after thorough preparation surface remains powdery, for best effect seal with 1 coat of Smart GP Wall Sealer 400. If the surface suffers from alkali attack, it is best recommended to seal with 1 coat of Smart Wall Sealer 800.

Painting Guide

Surface Condition	Sealer (1 coat)	Finish (1 - 2 coats)
Powdery Surface	Smart Green Sealer 850 Smart Eco Sealer Smart Wall Sealer 900 Smart Wall Sealer Super 5400	Smart Vinyl Glo Extra Clean
Alkali/ New Surface	Smart Green Sealer 850 Smart Eco Sealer Smart Wall Sealer 900 Smart Wall Sealer Super 5400	Smart Vinyl Glo Extra Clean

Company Identification

Manufacturer : Smart Paint Manufacturing Sdn. Bhd.
 No 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia
 Telephone No. : +607-863 9855 (Hunting Line) Fax No. : +607-861 5055
 Email : info@smart-paints.com