



DELUXE EMULSION

INTERIOR WALL FINISH



DURRA DELUXE EMULSION

DURRA DELUXE EMULSION 是精心配制的优质乳胶漆。它适用于涂饰户内的水泥墙石棉和各种木板。其高品质的全面性髹饰，能供室内持久、柔和与平滑的修饰。DURRA DELUXE EMULSION 是注重经济效应家居方案的最佳选择。

DURRA DELUXE EMULSION

DURRA DELUXE EMULSION dirumus khas untuk kegunaan di dalam rumah. Ia memberi sajian yang menarik, halus serta perlindungan kepada permukaan dinding, asbestos dan papan lembut serta keras. DURRA DELUXE EMULSION mudah disapu dan ia adalah pilihan yang disyorkan bagi skim perumahan yang mengutamakan ekonomi.

DURRA DELUXE EMULSION

DURRA DELUXE EMULSION is specially formulated emulsion paint for interior masonry. It provide an attractive smooth finish on walls, asbestos hard and soft boards. It is very easy to apply and is highly recommended for housing scheme where economy is priority.

表面处理

确保表面干净及彻底干透，绝无松散的污垢，油脂或腊迹。先把表面修平。为了取得最佳效果，请先涂上一层 Durra Eco Sealer 5100，然后再涂上两层 DURRA DELUXE EMULSION。重新髹漆时间相隔一至两小时。

Penyediaan Permukaan

Pastikan permukaan yang hendak dicat bersih, dinding yang kering sepenuhnya dan bebas daripada segala bahan cat yang menyerpih, kotoran, minyak atau lilin. Perbaiki permukaan yang rosak sebelum menyapu cat. Untuk hasil yang terbaik, sapu satu lapisan Durra Eco Sealer 5100 diikuti dengan dua lapisan DURRA DELUXE EMULSION. Biarkan selama 1-2 jam untuk pengeringan antara lapisan.

Surface Preparation

Ensure the wall surface to be painted is clean wall to dry out thorough and free from all defects or poor adhering material like dirt, grease or wax. Repair surface defect before painting. For best results, apply 1 coat of Durra Eco Sealer 5100 followed by 2 coats of DURRA DELUXE EMULSION. Allow 1-2 hours drying between coat.

施工资料

手触干度 : 视气温和湿度而定，
 髹次层漆 : 相隔一至两小时。
 髹扫面积 : 每公升十至十三平方公尺。
 层数 : 两层。

Data Penggunaan

Tempoh Kering : Bergantung kepada suhu dan kelembapan.
 Tempoh Lapisan Semula : 1 - 2 jam.
 Liputan Teori : 10 - 13m² per/litre.
 Jumlah Lapisan : 2 lapisan.

Application Data

Touch Dry : Dependent on temperature and humidity.
 Recoat : 1-2 hours.
 Coverage : 10 - 13m² per/litre.
 No. of coat : 2 coats.

用法

髹扫用具 : 使用前需彻底搅均。可用漆扫，油漆滚筒涂扫或喷射。
 调稀 : 通常不必调稀。如果需要调稀，可用不超过10%的清水进行稀释。
 清理 : 髹漆工作完成后，即刻用清水洗净工具。

Cara Penggunaan

Cara Penggunaan: Kacau sehingga sekata sebelum menggunakannya. Cat ini boleh disapu dengan berus, penggelek atau penyembur.
 Pencairan : Untuk kegunaan biasa, pencairan lazimnya tidak diperlukan. Jika perlu, cairkan dengan maksimum 10% air.
 Pencairan : Cuci perkakas dengan air bersih sebaik sahaja selesai kerja

Direction To Use

Application : Stir well before use. Application can be carried out by using brush, roller or spraying.
 Thinning : Use directly or dilute with a maximum of 10% water.
 Celaning Up : Clean all equipment with clean water immediately after use.



- ✓ Low VOC
- ✓ Low Odour
- ✓ Good Hiding Power
- ✓ Water Base, No Added Lead Or Mercury



DELUXE EMULSION

INTERIOR WALL FINISH



Manufacturing by :

SMART PAINT MANUFACTURING SDN BHD (1031014-A)

No. 9 & 11, Jalan Indah Gemilang 5, Taman Perindustrian Gemilang,
 81800 Ulu Tiram, Johor, Malaysia.

email : info@smart-paints.com www.smart-paints.com mysmartpaints





DELUXE EMULSION

INTERIOR WALL FINISH



- ✓ Low VOC
- ✓ Low Odour
- ✓ Good Hiding Power
- ✓ Water Base, No Added Lead Or Mercury



Also available in 9102 White & 9103 Black ★Premium Colour

The colours on this card are as close to the actual colours as modern printing techniques allow.